

DRAINING TROLLEY

AW 300 DL | Compressed air

Our draining trolleys are the result of our total commitment to quality, innovative technology, years of experience and consistent further development of tried and tested systems.

Typ AW 300 DL:

Large filter surface 420 X 970 mm
equivalent to 0.4 m²
Length 1500 mm
Width 500 mm
Height 1200 mm
Weight with accessories 200 kg
Capacity 300 l



DRAINING TROLLEY

AW 300 DL | Compressed air



Double perforated insert

- 1 5 mm Ø
- 1 Fine separation with 0,5 mm Ø



Cock 2" for tank cleaning




Sturdy chip chute



Accessories

- 1 Suction hose 2" x 3 m
- 1 Discharge hose 1 1/4" x 3 m
- 1 Compressed air hose 9 x 8 m nominal size
- 1 Round nozzle 50 mm inside with
- 1 Round nozzle 16 mm inside with
- 1 Flat nozzle 150 mm wide
- 1 Chip pusher



Air operated suction unit with high-performance silencer

- Air consumption: 900 l/min
- Negative pressure: 0.2 bar
- Optimal air connection: 6 bar
- Suction capacity with clean filter: 200 l/min
- pump: 230 V, 50 Hz, 3.93 A
H max. 8.6 m Q min. 100 l/min
H min. 3.8 m Q max. 250 l/min