

**Global expertise in
handling of Lubricants
and other fluids**

mato



MATO GmbH & Co. KG
Benzstr. 16-24
63165 Mühlheim a.M.
Germany
Tel.: +49 (0) 6108 - 906-0
Fax: +49 (0) 6108 - 906-120
www.mato.de
lubrication@mato.de



MATO Suisse AG
Industriestrasse 53
CH-6034 Inwil
Switzerland
Tel.: +41 (0) 41 - 4490990
Fax: +41 (0) 41 - 4490992
info@mato.ch
www.mato.ch



MATO Industries Ltd.
Lumatic Lubrication Division
26 Brunel Road
St Leonards on Sea, East Sussex
TN38 9RT United Kingdom
Tel.: +44 (0) 1424 - 851270
Fax: +44 (0) 1424 - 850091
sales@lumatic.co.uk



MATO France S.A.R.L.
2 rue du grunhof / ZA
F-57890 Porcellette
France
Tel.: +33 (0) 3 - 87821215
Fax: +33 (0) 3 - 87297213
mato.france@mato.de



MATO Iberica, S.L.
Pol. Industrial Mora Garay
Calle Marie Curie, parc. 36/38
E-33211 Gijón
Spain
Tel.: +34 (0) 985 - 328900 / 328211
Fax: +34 (0) 985 - 322647
matoiberica@matoiberica.es



MATO Corporation
201 Resource Drive
Beckley, WV 25801
West Virginia
USA
Tel.: +1 304 - 255 1280
Fax: +1 304 - 255 2501
info@mato-usa.com



MATO Australia Pty Ltd.
PO Box 3102
39 Bonville Avenue
Thornton NSW 2322
Australia
Tel.: +61 1300 - 850 795
Fax: +61 24936 - 1388
maus@mato.com.au



MATO Industrial Technologies
(Qufu) Co Ltd.
West End of Changchun Road
Development Zone of Qufu
273100 Qufu City, Shandong
PR China
Tel.: +86 537 - 4533799
Fax: +86 537 - 4533299
www.mato.com.cn



MATO Sib
Uliza Telefonnaja 15
Kemerovo
652523 Leninsk-Kusnezskij
Russian Federation
Tel.: +7 (0) 38456 35166
Fax: +7 (0) 38456 35166
mato-sib@yandex.ru



MATO Products Pty Ltd.
P.O. Box 224
Kempton Park 1620
28 Forge Road Spartan
South Africa
Tel.: +27 (0) 11 - 928 4163
Fax: +27 (0) 11 - 923 6071
matosales@multotec.co.za



Lube-Shuttle® is a registered trademark of MATO.
All photos used are protected by copyright. Any use of the photos without permission,
in what form ever, is prohibited and will be prosecuted under civil and criminal laws.

Lubrication Equipment - Fluid Handling Products



mato^{Lube-Shuttle®}

- **Clean & Easy!**
 - remove screw cap
 - screw in cartridge
- READY**



- **Economical & Ecological!**

- maximum cartridge discharge
- no air release necessary
- cartridge refillable
- permanent monitoring of grease-type and filling-level

- **Comprehensive Product-Range!**

The Lube-Shuttle® product range can not just replace what common lubrication equipment can achieve, it offers benefits in maintenance that go beyond.

Lube-Shuttle® side-lever grease gun

Side lever grease gun for Lube-Shuttle® system-cartridge, features **zinc plated steel pump-head, zinc plated cartridge protection tube** and ergonomic hand-grip, w.p.

more than 400 bar (5.800 psi), max. pressure approx. 800 bar (11.600 psi)

TÜV, DLG, BLT approved



Lube-Shuttle® one-hand grease gun

One-hand grease gun for Lube-Shuttle® system-cartridge, features zinc plated steel cartridge protection tube, ergonomic pistol-grip

max. w.p. approx. 300 bar (4.350 psi)



One-hand air operated grease gun for Lube-Shuttle® system-cartridges

designed for grease up to NLGI class 3, single shot system

output approx. 1 ccm per stroke, pressure ratio 1:60

max. pressure 480 bar (6.950 psi), air input-pressure 3 to max. 8 bar



All Lube-Shuttle® grease applicators are available with outlet-threadsize

- metric M10x1, R 1/8" BSP, NPT and various extensions:
- E4024 rigid pipe with 4-jaw hydraulic safety-coupler
- PH-30 high pressure nylon-hose, multiple braided, b.p. 1.000 bar (14.450 psi), ø 9 mm, with 4-jaw hydraulic safety-coupler
- RH-30 high pressure safety rubber hose, steel wire braide , b.p. 1.650 bar (23.900 psi), ø 13 mm, with 4-jaw hydraulic safety-coupler



Accu-Greaser 18 V Li-Ion

Battery-operated grease guns for Lube-Shuttle® system cartridges, available three different product lines **Standard, Premium und Professional.**

All versions feature a powerfull drive unit with 18 V DC motor and planetary gear that reaches peak pressure rates well above the 400 bar max. w.p. The greaser drive unit is equipped with an electric overload protection.

Further features:

- battery level display and overload indication bulb
- max. promotion approx. 115 ccm per minute
- cartridge protection tube with Lube-Shuttle® embossing
- high pressure safety rubber hose, 1.650 b.p., lenght 750 mm, incl. 4-jaw hydraulic safety-coupler, thread R 1/8"
- sturdy but compact transport case with cavities to fit cartridges and accessories

Accu-Greaser 18 V Standard-LS incl.

- Li-Ion battery 18 V - 1.500 mAh
- standard charger, wide range input, 100-240 V AC / 50-60 Hz with overload protection, charging time approx. 60 min.

Accu-Greaser 18 V Premium-LS incl.

- Li-Ion battery 18 V - 1.500 mAh
- multi-charger, wide range input, 12-240 V AC / 50-60 Hz with overload protection, charging time approx. 80 % in 20 min. and 100 % in 40 min., port for 12/24 V vehicle power supply cable

Accu-Greaser 18 V Professional-LS incl.

- Li-Ion battery 18 V - 4.000 mAh
- multi-charger, wide range input, 12-240 V AC / 50-60 Hz with overload protection, charging time approx. 80 % in 50 min. and 100 % in 100 min., port for 12/24 V vehicle power supply cable
- 12/24 V vehicle power supply cable
- shoulder strap



LubeJet-eco grease spray applicator

This air operated grease spray unit enables the spraying of grease directly from the Lube-Shuttle® system-cartridge without the need for propellants or chemical additives, such as solvents.

Spraying grease onto chains, wire ropes, open gears, slideways, telescopic booms etc. offers enormous potential for cost savings. Eliminates wasteful consumption of grease in surface coating, offers wide range of applications.



Lube-Shuttle® dispenser Lube-Shot 400

Designed to apply grease to all open surfaces, i.e. uncaged roller bearings. The dispenser will replace traditional, messy methods of application with open cartridges and brushes. The use of this dispenser will permit clean and uncontaminated greasing of open bearings. Lube-Shot 400 with nozzle, screw cap and an adaptor nozzle for the Lube-Shuttle® system-cartridge.



Lube-Shuttle® accessories

To get acquainted with the Lube-Shuttle® product range we offer **five different greases**, with different properties (basic, PLUS, Graphite, High Temp, Protect).

The **Lube-Shuttle® refill adaptor** can be mounted to manual or pneumatic pail-mounted grease transfer pumps to conveniently refill empty Lube-Shuttle® system cartridges.

